




Geberit Kombifix element for wall-hung WC, 109 cm, with Sigma concealed cistern 8 cm



APPLICATION PURPOSES

- For masonry walls
- For installation in part or room-height prewall installations
- For wall-hung WCs with connection dimensions in accordance with EN 33:2011
- For single flush, dual flush or stop-and-go flush

CHARACTERISTICS

- Range 2016
- Powder-coated mounting frame
- Mounting frame with four fastening brackets
- Premounted direct plastering netting
- Fixing bracket coordinated with solid walls with 8 or 12 cm wall thickness
- Fastening for connection bend can be mounted without tools from front
- Concealed cistern with front actuation
- Concealed cistern, fully insulated against condensation

- Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the top left
- Protection box for service opening can be cut to length, suitable for surface-even actuator plates
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- Fastening option for electrical connection

TECHNICAL DATA

Flow pressure	0.1–10 bar
Flush volume, factory setting	6 / 3 l
Flush volume large, adjustment range	4 / 4.5 / 6 / 7.5 l
Flush volume small, adjustment range	2–4 l
Product material	Steel
Height-adjustable	No

SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- Protection box for service opening
- 4 fixing brackets
- Connection set for WC, $\varnothing$ 90 mm
- Connection bend 90° made of PE-HD, $\varnothing$ 90 mm
- Adapter socket made of PE-HD, $\varnothing$ 90 / 110 mm
- 2 protection plugs
- 2 threaded rods M12
- Fastening material

ACCESSORIES

- Geberit Kombifix set of leg supports
- Geberit Kombifix set of studs with foot plate

INFO

- Actuator plate has to be ordered separately

Art. no.	B cm	H cm	T cm
110.792.00.1	42	109	8