



Geberit Duofix element for urinal, 112–130 cm, universal



APPLICATION PURPOSES

- For metal and wood frame walls
- For Geberit Duofix system walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For floor constructions 0–25 cm

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- With pull-out plate for lateral fastening above the element on metal or wood profiles or on Geberit Duofix system studs
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components
- Galvanised non-slip leg supports protected against corrosion
- Water supply connection compatible with MasterFix and MeplaFix
- Elbow connector can be mounted without tools
- Premounted stop valve with throttle

- Flush hose can be bent
- Flush hose with guide to prevent standing water
- Fastening for inlet $\varnothing$ 32 mm, height-adjustable
- Fastening for connection bend, height-adjustable and sound-absorbing
- Urinal fasteners M8 width- and height-adjustable
- Crossbars with centring marks, adjustable without tools
- Can be refitted with accessories to fit urinals with spray head

TECHNICAL DATA

Flow pressure	1–8 bar
Water test pressure max.	16 bar
Test pressure air / inert gas max.	3 bar
Durchfluss bei 100 kPa / 1 bar ohne Durchflussbegrenzer	0.3 l/s
Durchfluss bei 100 kPa / 1 bar mit Durchflussbegrenzer	0.18 l/s
Product material	Steel
Height-adjustable	Yes

SCOPE OF DELIVERY

- Elbow tap connector R 1/2"

- Protection box with cover
- Connection pipe between inlet $\varnothing$ 32 mm and urinal, with seal to urinal
- Connection bend made of PE-HD, $\varnothing$ 63 / 50 mm
- Seal $\varnothing$ 57 / 50 mm
- Urinal trap $\varnothing$ 50 mm, with seal on urinal
- Fastening and protection material

ACCESSORIES

- Geberit Duofix set of wall anchors for single installation
- Geberit Duofix set of wall anchors for single and system installation
- Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchor extensions
- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- Geberit Duofix set of foot fastener on rear wall
- Geberit Duofix set of foot extensions 20 cm length
- Geberit inlet crossbar for urinal, with spray head

INFO

- For urinals with spray head, the Geberit inlet crossbar for urinal (art. no. 242.042.00.1) is required in addition

Art. no.	B cm	H cm	T cm
111.616.00.2 New	50	112–130	7.5

New article available from 01.07.2025